

accessory 3VJ9 IEC framesize 3VJ10 125A shunt trip 220VAC 50/60Hz

| Model                                   |                           |
|-----------------------------------------|---------------------------|
| product designation                     | shunt                     |
| design of the product                   | accessory for 3VJ breaker |
| accessories                             | auxiliary release         |
| General technical data                  |                           |
| degree of pollution                     | 3                         |
| consumed active power / at DC / maximum | 50 W                      |
| Voltage                                 |                           |
| control supply voltage (Us) / at AC     | 220 V AC                  |
| Mechanical Design                       |                           |
| net weight                              | 38 g                      |
| ambient temperature / during operation  |                           |
| • minimum                               | -10 °C                    |
| • maximum                               | 60 °C                     |
| ambient temperature / during storage    |                           |
| • minimum                               | -15 °C                    |
| • maximum                               | 75 °C                     |
| ambient temperature / during storage    |                           |
| • minimum                               | -15 °C                    |
| • maximum                               | 75 °C                     |
| ambient temperature / during operation  |                           |
| • minimum                               | -10 °C                    |
| • maximum                               | 60 °C                     |
| Connections according IEC               |                           |
| stripped length                         | 10 mm                     |
| connectable conductor cross-section     |                           |
| • minimum                               | 0.14 ... 0.16             |
| • maximum                               |                           |
| Certificates                            |                           |
| other                                   |                           |

[Confirmation](#)

### Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VJ9018-0ST36>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VJ9018-0ST36>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3VJ9018-0ST36](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VJ9018-0ST36)

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



