

### product type designation



### CM 1243-5

communications module CM 1243-5 for connection of SIMATIC S7-1200 to PROFIBUS as DP Master module; PG/OP communication; S7 communication.

transfer rate	
transfer rate	
<ul style="list-style-type: none"> <li>at the 1st interface / according to PROFIBUS</li> </ul>	9.6 kbit/s ... 12 Mbit/s
interfaces	
number of interfaces / according to Industrial Ethernet	0
number of electrical connections	
<ul style="list-style-type: none"> <li>at the 1st interface / according to PROFIBUS</li> </ul>	1
<ul style="list-style-type: none"> <li>for power supply</li> </ul>	1
type of electrical connection	
<ul style="list-style-type: none"> <li>at the 1st interface / according to PROFIBUS</li> </ul>	9-pin Sub-D socket (RS485)
<ul style="list-style-type: none"> <li>for power supply</li> </ul>	3-pole terminal block
supply voltage, current consumption, power loss	
type of voltage / of the supply voltage	DC
supply voltage / external	24 V
supply voltage / external / at DC / rated value	24 V
relative positive tolerance / at DC / at 24 V	20 %
relative negative tolerance / at DC / at 24 V	20 %
consumed current	
<ul style="list-style-type: none"> <li>from external supply voltage / at DC / at 24 V / typical</li> </ul>	0.1 A
power loss [W]	2.4 W
ambient conditions	
ambient temperature	
<ul style="list-style-type: none"> <li>for vertical installation / during operation</li> </ul>	0 ... 45 °C
<ul style="list-style-type: none"> <li>for horizontally arranged busbars / during operation</li> </ul>	0 ... 55 °C
<ul style="list-style-type: none"> <li>during storage</li> </ul>	-40 ... +70 °C
<ul style="list-style-type: none"> <li>during transport</li> </ul>	-40 ... +70 °C
relative humidity	
<ul style="list-style-type: none"> <li>at 25 °C / without condensation / during operation / maximum</li> </ul>	95 %
protection class IP	IP20
design, dimensions and weights	
module format	Compact module S7-1200 single width
width	30 mm
height	100 mm
depth	75 mm
net weight	0.134 kg
fastening method	
<ul style="list-style-type: none"> <li>35 mm DIN-rail mounting</li> </ul>	Yes
<ul style="list-style-type: none"> <li>S7-300 rail mounting</li> </ul>	No

<ul style="list-style-type: none"> <li>• wall mounting</li> </ul>	Yes
<b>product features, product functions, product components / general</b>	
number of units	
<ul style="list-style-type: none"> <li>• per CPU / maximum</li> </ul>	3
<b>performance data / PROFIBUS DP</b>	
service / as DP master	
<ul style="list-style-type: none"> <li>• DPV1</li> </ul>	Yes
number of DP slaves	
<ul style="list-style-type: none"> <li>• on DP master / operable</li> </ul>	32
data volume	
<ul style="list-style-type: none"> <li>• of the address range of the inputs / as DP master / total</li> </ul>	512 byte
<ul style="list-style-type: none"> <li>• of the address range of the outputs / as DP master / total</li> </ul>	512 byte
<ul style="list-style-type: none"> <li>• of the address range of the inputs / per DP slave</li> </ul>	244 byte
<ul style="list-style-type: none"> <li>• of the address range of the outputs / per DP slave</li> </ul>	244 byte
<ul style="list-style-type: none"> <li>• of the address range of the diagnostic data / per DP slave</li> </ul>	240 byte
service / as DP slave	
<ul style="list-style-type: none"> <li>• DPV0</li> </ul>	No
<ul style="list-style-type: none"> <li>• DPV1</li> </ul>	No
<b>performance data / S7 communication</b>	
number of possible connections / for S7 communication	
<ul style="list-style-type: none"> <li>• maximum</li> </ul>	8; max. 4 connections to other S7 stations
<ul style="list-style-type: none"> <li>• with PG connections / maximum</li> </ul>	1
<ul style="list-style-type: none"> <li>• with PG/OP connections / maximum</li> </ul>	3
<b>performance data / multi-protocol mode</b>	
number of active connections / with multi-protocol mode	
<ul style="list-style-type: none"> <li>• without DP / maximum</li> </ul>	8
<ul style="list-style-type: none"> <li>• with DP / maximum</li> </ul>	8
<b>performance data / telecontrol</b>	
protocol / is supported	
<ul style="list-style-type: none"> <li>• TCP/IP</li> </ul>	No
<b>product functions / management, configuration, engineering</b>	
configuration software	
<ul style="list-style-type: none"> <li>• required</li> </ul>	STEP 7 Basic/Professional
product function / is supported / identification link	Yes; acc. to IEC 61406-1:2022
<b>standards, specifications, approvals</b>	
reference code	
<ul style="list-style-type: none"> <li>• according to IEC 81346-2:2019</li> </ul>	KEC
<b>standards, specifications, approvals / Environmental Product Declaration</b>	
Environmental Product Declaration	Yes
global warming potential [CO2 eq]	
<ul style="list-style-type: none"> <li>• total</li> </ul>	89.58 kg
<ul style="list-style-type: none"> <li>• during manufacturing</li> </ul>	14.29 kg
<ul style="list-style-type: none"> <li>• during operation</li> </ul>	75.11 kg
<ul style="list-style-type: none"> <li>• after end of life</li> </ul>	0.18 kg
<b>further information / internet links</b>	
internet link	
<ul style="list-style-type: none"> <li>• to website: Selection guide for cables and connectors</li> </ul>	<a href="https://support.industry.siemens.com/cs/ww/en/view/109766358">https://support.industry.siemens.com/cs/ww/en/view/109766358</a>
<ul style="list-style-type: none"> <li>• to web page: selection aid TIA Selection Tool</li> </ul>	<a href="https://www.siemens.com/tstcloud">https://www.siemens.com/tstcloud</a>
<ul style="list-style-type: none"> <li>• to website: Industrial communication</li> </ul>	<a href="https://www.siemens.com/simatic-net">https://www.siemens.com/simatic-net</a>
<ul style="list-style-type: none"> <li>• to web page: SiePortal</li> </ul>	<a href="https://sieportal.siemens.com/">https://sieportal.siemens.com/</a>
<ul style="list-style-type: none"> <li>• to website: Image database</li> </ul>	<a href="https://www.automation.siemens.com/bilddb">https://www.automation.siemens.com/bilddb</a>
<ul style="list-style-type: none"> <li>• to website: CAx-Download-Manager</li> </ul>	<a href="https://siemens.com/cax">https://siemens.com/cax</a>
<ul style="list-style-type: none"> <li>• to website: Industry Online Support</li> </ul>	<a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>
<b>security information</b>	
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected

to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit [www.siemens.com/cybersecurity-industry](http://www.siemens.com/cybersecurity-industry). Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under <https://www.siemens.com/cert>. (V4.7)

**Approvals / Certificates**

**General Product Approval**



EG-Konf.

[Declaration of Conformity](#)



CCC



[China RoHS](#)

**General Product Approval**

**EMV**

**For use in hazardous locations**



UL



RCM

[KC](#)



ATEX



IECEx

[EM](#)

**For use in hazardous locations**

**Maritime application**

[CCC-Ex](#)



ABS



BUREAU VERITAS



DNV



LRS

[NK / Nippon Kaiji Kyokai](#)

**Maritime application**

**Environment**



RINA



EPD

last modified:

2/28/2025