



SIMATIC ET 200SP, BaseUnit BU15-P16+A0+2B, BU type A0, Push-in terminals, without AUX terminals, bridged to the left, WxH: 15x 117 mm

Figure similar

General information	
Product type designation	BU type A0
HW functional status	From FS06
Supply voltage	
Rated value (DC)	24 V
external protection for power supply lines	Yes; 24 V DC/10 A miniature circuit breaker with type B or C tripping characteristic
Mains filter	
<ul style="list-style-type: none"> integrated 	No
Current carrying capacity	
For P1 and P2 bus, max.	10 A
For process terminals, max.	2 A
Hardware configuration	
Automatic encoding	Yes
Formation of potential groups	
<ul style="list-style-type: none"> New potential group Potential group continued from the left 	No Yes
Slots	
<ul style="list-style-type: none"> Number of slots 	1; Type A0
Isolation	
Isolation tested with	707 V DC (type test)
Standards, approvals, certificates	
Ecological footprint	
<ul style="list-style-type: none"> environmental product declaration 	Yes
Global warming potential	
— global warming potential, (total) [CO2 eq]	0.873 kg
— global warming potential, (during production) [CO2 eq]	0.866 kg
— global warming potential, (during operation) [CO2 eq]	0 kg
— global warming potential, (after end of life cycle) [CO2 eq]	-0.0011 kg
Ambient conditions	
Ambient temperature during operation	
<ul style="list-style-type: none"> horizontal installation, min. horizontal installation, max. vertical installation, min. vertical installation, max. 	-30 °C 60 °C -30 °C 50 °C
Altitude during operation relating to sea level	
<ul style="list-style-type: none"> Installation altitude above sea level, max. 	5 000 m; Restrictions for installation altitudes > 2 000 m, see manual

Accessories

Color coding labels

- for process terminals CC00 to CC09
- for AUX terminals does not exist
- for add-on terminals does not exist

connection method

Terminals

- Terminal type Push-in terminal
- system-integrated shield connection Yes; Optional
- Conductor cross-section, min. 0.14 mm²; AWG 26
- Conductor cross-section, max. 2.5 mm²; AWG 14
- Number of process terminals to I/O module 16; Pro slot
- Number of terminals to AUX bus 0
- Number of add-on terminals 0
- Number of terminals with connection to P1 and P2 bus 2; Pro slot

Dimensions

Width	15 mm
Height	117 mm
Depth	35 mm

Weights

Weight, approx.	40 g
-----------------	------

Classifications

	Version	Classification
eClass	14	27-24-26-03
eClass	12	27-24-26-03
eClass	9.1	27-24-26-03
eClass	9	27-24-26-03
eClass	8	27-24-26-03
eClass	7.1	27-24-26-03
eClass	6	27-24-26-03
ETIM	9	EC001598
ETIM	8	EC001598
ETIM	7	EC001598
IDEA	4	3560
UNSPSC	15	32-15-17-04

Approvals / Certificates

General Product Approval



EG-Konf.



[Manufacturer Declaration](#)



UL

[KC](#)



RCM

For use in hazardous locations



UL

[FM](#)

[CCC-Ex](#)



ATEX



IECEX

[Miscellaneous](#)

Maritime application



ABS



BUREAU
VERITAS



DNV



LRS

[NK / Nippon Kaiji Kyokai](#)



RINA



[CCS \(China Classification Society\)](#)



last modified:

4/7/2025