



Door mounting kit IP65 for HMI module

product brand name	SIRIUS
product category	HMI modules
product designation	Door mounting kit
design of the product	IP65
product type designation	3RW59
manufacturer's article number of soft starter	
•	3RW50
•	3RW51
•	3RW52
•	3RW55

**General technical data**

Substance Prohibitation (Date)	02/15/2018
Weight	0.043 kg

**Ambient conditions**

ambient temperature during storage and transport	-40 ... +80 °C
--	----------------

**Electrical Safety**

protection class IP on the front according to IEC 60529	IP20
touch protection on the front according to IEC 60529	finger-safe, for vertical contact from the front

**Approvals Certificates**

General Product Approval	EMV	For use in hazardous locations
--------------------------	-----	--------------------------------



[KC](#)

[Miscellaneous](#)

**Test Certificates**      **Maritime application**

[Type Test Certificates/Test Report](#)



**other**      **Environment**



[Confirmation](#)

[Environmental Confirmations](#)

## Further information

### Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

### Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

### Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RW5980-0HD00>

### Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RW5980-0HD00>

### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5980-0HD00>

### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RW5980-0HD00&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RW5980-0HD00&lang=en)

### Characteristic: Tripping characteristics, I<sup>2</sup>t, Let-through current

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5980-0HD00/char>

### Characteristic: Installation altitude

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RW5980-0HD00&objecttype=14&gridview=view1>

### Simulation Tool for Soft Starters (STS)

<https://support.industry.siemens.com/cs/ww/en/view/101494917>

---

last modified:

4/2/2025 

